

ExaGrid® EX1000 to EX5000 Appliance Series



Application Support

Backup Applications (File, Database, Email)

- CA ARCserve - 11.5, 12.0, 12.5
- Symantec Backup Exec - 11D, 11.5, 12.0, 12.5, 2010/OST
- Symantec NetBackup - 6.0, 6.5.x, 7.0/OST
- CommVault Simpana - 7.0, 8.0
- EMC NetWorker - 7.3, 7.4, 7.5, 7.6
- VMware files (VMDK) via supported backup applications and VMDK direct backups
- Vizioncore vRanger Pro - 3.x, 4.x
- Oracle Recovery Manager (RMAN) - 10 and 11

Backup Applications (continued)

- SQL Server 2000 & 2005 Dumps
- Unix/Linux File System Dumps

Operating System File Backup

- Microsoft Windows
- Linux
- Novell NetWare
- UNIX

Backup Application Storage Protocol Support

- CIFS (Windows)
- NFS (UNIX / Linux)

Site Configuration

Primary Site Configuration

- Scalable from 250GB to 10TB per single appliance

Multi-site Support

- Supports up to 8 remote sites transferring data to a central site for a total of 9 sites
- Standard IP WAN connection between sites

Site Power Requirements

- Three NEMA 5-15R 3-prong receptacles per appliance
- Voltage: 100-240 VAC
- AMPS: 6.4 - 3.2 A
- Power: (typical) 490W
- Country kits available for international orders

Operating Temperature

- 10° to 35°C (50° to 95°F)
- Cooling: 2000 BTU/Hr.

Operating Relative Humidity

- 20% to 80% (non-condensing)

Regulatory Approvals (US, Canada, EU)

Safety

- ANSI/UL 60950; Update 1
- IEC 60950 -1:2001, MOD
- CSA C22.2 NO 60950 -1-03

Emissions

- FCC Class A
- EN55022

Immunity

- EN55024
- EN61000

Agency

- RoHS compliant
- WEEE Declaration for E.U. Directive

System Hardware Components

ExaGrid Server

- Intel Xeon Quad-core processors
- Intel Motherboard
- Enterprise SATA drives
- RAID6 with hot spare
- ExaGrid software
- 3U, 19-inch, rack-mount chassis
- Redundant fans
- Mirrored hot-plug power supplies
- Qty 2 10/100/1000 Ethernet ports for EX1000, EX2000, EX3000
- Qty 4 10/100/1000 Ethernet ports for EX4000, EX5000
- Qty 2 10 GbE ports for EX4000, EX5000 (optional, CX4 or SPF+)